



SFD Lite Report

Habiganj Municipality Bangladesh

This SFD Lite Report was prepared by
CWIS-FSM Support Cell, DPHE

Date of production: 11/11/2022

Last update: 29/02/2024

1 The SFD Graphic




Figure 1: SFD Graphic for Habiganj Municipality.

2 SFD Lite information

Produced by:

- Dr. Abdullah Al-Muyeed, Chief Operating Officer, CWIS-FSM Support Cell, Shishir Kumar Biswas, Project Director, 'Feasibility for Implementing of Solid Waste and Faecal Sludge Management System in 53 District Level Municipalities and 8 Municipalities', Department of Public Health Engineering (DPHE) and Md. Tawhidur Rahaman, Technical Expert, CWIS-FSM Support Cell, Department of Public Health Engineering (DPHE), Bangladesh.

Collaborating partners:

- DevCon, Tiller and Habiganj Municipality played vital roles in collecting and sharing data, and producing this SFD graphic and SFD lite report.

Date of production: 11/11/2022

3 General city information

Habiganj is a fast-growing city, which is 159 km away from the Dhaka city. It is beside the Khowai River and well connected with road and water. It is one of the oldest towns in the sub-continent and was declared Municipality in 1881. Habiganj is one of the 53 district level municipalities in the country. (Figure 2).




Figure 2: Habiganj Municipality Location Map (BBS 2017).

According to the population census in 2011 by the Bangladesh Bureau of Statistics (BBS), the Habiganj city population was 69,512. The urban population growth in Bangladesh is 3.5% per year. Considering 10% floating population, such as farmers and traders, comes to the city every day, the present (2020) population is estimated to be around 93,828 (Table 1).

Table 1: City profile (Source: KII with the Executive Engineer, Habiganj Municipality).

Population Parameters	Value
Estimated population, 2020	93,828
Households, 2020	20,070
Area, sq.km	8.97
Total roads, km	145
Total drains, km	80

The municipality covers an area of 8.97 square kilometres (Figure 3). The current population of Habiganj Municipality is nearly 1 *lakh*¹. At present Habiganj Municipality has 145 km of road. The city has about 80 km of drain which includes 65 km Reinforced Cement Concrete (RCC) and 15km earthen drain.² The maximum mean temperature observed is 32-32.9°C between April-August, with the minimum mean temperatures of between 9.5-11.3°C in January. The annual average rainfall is about 23.55 mm, according to BMD (1981-2017).



¹ 1 lakh = 100,000

² Source: 'At a Glance: Habiganj Municipality', by Municipality office

Figure 3: Habiganj Municipality Ward Boundary Map (BBS, 2017).

According to the Bangladesh Meteorological Department, the city area and surrounding area experiences a tropical monsoon climate. It is characterized by warm, humid summers and cool, and dry winters. There is no climatological station within the municipality. The closest meteorological station of Bangladesh Meteorological Department is located in Sreemangal which is about 32 km away from the municipality area. Weather data from this station are collected from 1981 to 2017. About 90% of the total annual rainfall occurs in the period from May through October and the driest months of the years are November to March.

Khowai River flows beside the municipality. According to the flood zoning map of Bangladesh (BMD, 2012), the city is in a flood prone zone (flooding event occurred in the last 12 years). However, the drainage network of the city is not adequate. Every year, many areas face water logging during monsoon for drainage congestion. There are some secondary drains carrying stormwater and domestic wastewater to the outfalls the rivers and canals.

The household survey results show that majority of the occupation is business (42%) followed by Government Service (10%) and private service (10%). The survey assessed the different types of building structure in the city which are pucca (houses single or multi-storied built with substantial materials such as brick, cement, and concrete), semi pucca houses (either the roof or the walls, but not both, are not made of pucca materials), Tin-shed (roof of the house mad of corrugated iron sheets) and thatched (roof and walls made of temporary materials like bamboo, paper boards, polyethylene sheets, etc.

4 Service outcomes

The city does not have a dedicated sewerage system and most sanitation systems available in the town are classified as onsite systems (97.0%). The main types of toilet facilities are septic tanks connected to a soak pit, to an open drain, to a water body, to open ground and to 'don't know where', lined tanks and lined pits, with no outlet or overflow.

Table 2 summarizes the sanitation systems in use, as well as estimates of the population connected to each system. For the onsite sanitation systems, it shows the proportions of each from which faecal sludge is then emptied, transported to treatment and treated.

Habiganj Municipality, Habiganj , Bangladesh, 11 Nov 2022. SFD Level: SFD Lite								
Population: 93828								
Proportion of tanks: septic tanks: 71%, fully lined tanks: 0%, lined, open bottom tanks: 100%								
Containment								
System type	Population	WW transport	WW treatment	FS emptying	FS transport	FS treatment	SN transport	SN treatment
	Pop	W4c	W5c	F3	F4	F5	S4e	S5e
System label and description	Proportion of population using this type of system (p)	Proportion of wastewater in open sewer or storm drain system, which is delivered to treatment plants	Proportion of wastewater delivered to treatment plants, which is treated	Proportion of this type of system from which faecal sludge is emptied	Proportion of faecal sludge emptied, which is delivered to treatment plants	Proportion of faecal sludge delivered to treatment plants, which is treated	Proportion of supernatant in open drain or storm sewer system, which is delivered to treatment plants	Proportion of supernatant in open drain or storm sewer system that is delivered to treatment plants, which is treated
T1A1C6 Toilet discharges directly to open drain or storm sewer	3.0	0.0	0.0					
T1A2C5 Septic tank connected to soak pit	7.7			55.0	0.0	0.0		
T1A2C6 Septic tank connected to open drain or storm sewer	34.8			53.0	0.0	0.0	0.0	0.0
T1A2C7 Septic tank connected to open water body	10.2			53.0	0.0	0.0		
T1A2C8 Septic tank connected to open ground	6.7			53.0	0.0	0.0		
T1A2C9 Septic tank connected to 'don't know where'	0.2			53.0	0.0	0.0		
T1A4C10 Lined tank with impermeable walls and open bottom, no outlet or overflow	9.0			86.0	0.0	0.0		
T1A5C10 Lined pit with semi-permeable walls and open bottom, no outlet or overflow	28.4			78.0	0.0	0.0		

Table 2: SFD Matrix for Habiganj Municipality.

The figures shown in Table 2 and elaborated in the following section are derived from information obtained through Household (HH) survey, Key Informant Interviews (KIIs), and Focus Group Discussions (FGDs) (as shown in Figure 4).

Overview on technologies and methods used for different sanitation systems through the sanitation service chain is as follows.

4.1 Offsite Systems

The city does not have a dedicated sewerage system. However, during field observation and HH survey, it was found that there is a certain area where toilets are directly connected to open drains or storm sewer. Similarly, a portion of septic tanks is directly connected to open drains or storm sewer. Therefore, T1A1C6 system is considered as 3.0% of the total population of the city to generate the SFD graphic. Similarly, the T1A2C6 system is considered 34.8% of the total population of the city to generate the SFD graphic. In the absence of a sewerage system, the faecal sludge and the supernatant in T1A2C6 are directly discharged into the river or the environment untreated.

4.2 On-site Sanitation Systems



Figure 4: Household survey and consultations. (Source: *Feasibility study 2020-21/DPHE*).

Containment: Almost all the households (97.0%) in the city have their latrine which is connected to single pits, twin pits, septic tanks, or discharged directly into the environment (e.g., open-drain or storm sewer). From a household survey, it is found that 59.6% of the city population uses septic tanks as the containment system, 28.4% of the toilets have single pit systems, and 9.0% of people use double pits in the city. About 3% do not have any type of containment and discharges directly to the environment (KII, FGDs, HH survey, 2020).

According to the type of connectivity and features of containment technologies, the discharging points of the toilets are categorized as: 7.7% population uses septic tanks connected to soak pits (T1A2C5), 34.8% population uses septic tanks connected to open drain (T1A2C6), 10.2% population uses septic tanks connected to water bodies (T1A2C7), 6.7% population uses septic tanks connected to open ground (T1A2C8), 0.2% have septic tanks connected to 'don't know where', 9.0% population uses lined tanks with impermeable walls and open bottom no outlet or overflow (T1A4C10) and 28.4% of the population relies on lined pits with semi-permeable walls and open bottom with no outlet or overflow (T1A5C10) (KII, FGDs, HH survey, 2020). Thus, at the containment stage, the city's excreta of only 45% of the population are contained. Figure 6 shows pictures of these technologies in operation.

Groundwater Pollution: The depth to groundwater in the city ranges from 1-3 m. The most common drinking water production technology is a borehole with a hand pump or motorized pump. Among them, 43% of the households use piped water, 24% use own hand pump tubewell and about 11% of the households use their own tubewell fitted with electric motor.

Lateral separation between sanitation facilities and water sources varies from one area to another. Tube wells of different sizes and depths are generally used to pump water from the subsurface confined aquifers.




Figure 5: Soil profile in Habiganj district and location of tubewell screen.

During the household visit and FGDs, it was found that less than 25% of sanitation facilities are located within 10 metres from the groundwater source. Besides, due to the geographical situation, sanitation facilities are not located uphill of the groundwater sources. According to a survey report on 'Hydrogeological screening, slug test and geophysical logging on observation well units', conducted by the Department of Public Health Engineering (DPHE) on March 2017, drinking water is collected from the confined aquifer (25m – 200m) through pumps. Hence, considering all these factors, it is considered that there is not any significant risk of groundwater contamination in the city. Therefore, a low risk of groundwater contamination is considered in the city.



Figure 6: Containment technologies and their connections in Habiganj. Left: Toilet Pit open to a nearby water body, Right: Toilet pipe connected to open environment. (Source: Feasibility study 2020-21/DPHE).

Emptying: Households relying on septic tanks have to arrange themselves for emptying of the septic tank. It is observed from the baseline survey that most of the septic tanks have been constructed in the last 4-5 years. According to the survey from 2020, the frequency of emptying of septic tanks or covered pits varies from 1 to 10 years depending upon the size, uses, etc.

However, about 55% of the septic tanks, connected to the soak pit are emptied within 2-5 years. About 53% of the septic tanks connected to open drains, open ground, water bodies or 'don't know where' are emptied within 4-5 years. Almost 78% of single pit latrines are emptied within 1-2 years. Besides the above information, it is also revealed during the discussion in FGDs and household visits, the demand for desludging septic tanks would increase shortly. Desludging of the septic tanks or pit is mostly (97%) done by private sweepers. Only in a few households, desludging is done by municipal sweepers (1.42%), family members (1.08%), and private agencies less than one percent (0.5%). Around 94% of this withdrawal is done manually using a bucket and rope. This method highly risks the health and safety of the workers. A few number (4%) use electric pumps and some use manual pump (2%) – these reflect the use of the higher level of technologies by some of the workers. The Municipality has one vacutug available³.

Transportation: The sludge withdrawn from the septic tanks and latrine pits by the cleaners is disposed of in various places. Based on the survey from 2020, it is observed that about 81.9% of the respondents who use any kind of containment system informed that faecal sludge (sludge from the septic tank or covered pit latrines) is disposed of in a dug hole covered with soil away from the house. Besides, 18.1% of the faecal sludge is disposed of in the open environment like a drain, open ground, and water bodies.

Treatment/Disposal: Presently, there are no treatment facilities in the town.

4.3 Open Defecation

From HH surveys, KIIs and FGDs, it was found that 100% of citizens use some kind of toilet in the municipality. Thus, from the sanitation point of view, the town is considered an open defecation-free town.

4.4 SFD Graphic

The outcome of the SFD graphic shows that only twelve percent (12%) of the excreta flow is classified as safely managed, and the remaining eighty eight percent (88%) is classified as unsafely managed (Figure 7).

³ In the last few years, mechanical vacuum trucks have been provided to several municipal authorities from different government and non-government sources. But municipal authorities have shortage of expert manpower and service delivery mechanism to operate the vehicles. Recent years, the situation is improving. Institutional Regulatory Framework (IRF) and National Action Plan (NAP) have been approved by government. Different service delivery and business models have been developed in few cities. Capacity building program of local government institutions are conducting by govt. institutions and development partners. A significant improvement in FSM will be found within few years.




Figure 7: SFD Graphic for Habiganj Municipality.

The unsafely managed excreta originated from wastewater not delivered to treatment (3%), Faecal Sludge (FS) both contained and not contained - not delivered to treatment (52%), FS not contained - not emptied (22%) and 10% of supernatant not delivered to treatment.

The safely managed excreta originate from FS contained - not emptied (12%). This 12% resembles the FS stored in containments without significant risk to groundwater pollution. Thus, the safely managed percentage of FS generated by this 12% of the population is temporary until the FS from the containments is emptied. Therefore, these systems will require emptying services in the short and medium term as they fill up.

5 Data and assumptions

The baseline survey conducted in September 2020 contains detailed data on different stages of the sanitation value chain. The SFD matrix is generated from these data, collected during sample household surveys, along with informal interviews, open-ended consultations, key informant interviews and focus group discussions with the Municipality officials, town level coordination committee, households, social workers, business persons, pit emptiers and the citizens including women in all the wards of the Municipality. The SFD matrix was generated from these data. Finally, data from all these sources were triangulated to produce the SFD matrix, the SFD graphic and the SFD lite report.

The last census was carried out about 10 years ago. So, the actual population, household, and sanitation data are not updated yet. Most of the households with septic tanks do not know the actual type, size, and design desludging periods. Also, a large number of pit users are unaware of the emptying events and frequency of their pits or not. Due to all these data gaps, some assumptions have been made to produce the SFD graphic. These assumptions were shared with key informants at the Municipality and accepted by them.

Following assumptions were made for developing the SFD graphic for Habiganj Municipality:

- ✓ The proportion of FS in septic tanks, fully lined tanks, and lined, open bottom tanks are considered 71%, 0%, and 100% respectively as per the guidance given in the Frequently Asked Questions (FAQs) in the Sustainable Sanitation Alliance (SuSanA) website.
- ✓ According to the population census in 2011 by the Bangladesh Bureau of Statistics (BBS), the population of Habiganj Municipality was 51,346. The urban population growth in Habiganjis 1.5% per year. Considering 10% floating population, such as farmers and traders, comes to the city every day, the present (2020) population is estimated to be around 93,828.
- ✓ There are around 9.0% of twin pit latrines in the containment system. So, it is assumed that all these twin pit containment technologies are defined as a lined tanks with impermeable walls and open bottom (system T1A4C10, 9.0%). Based on the household survey, variable F3 for system T1A4C10 is set to 86%.
- ✓ There are around 28.4% of single pit latrines in the containment systems. So, it is assumed that all these single pit containment technologies are defined as lined pits with semi-permeable walls and open bottom, no outlet or overflow, where there is no 'significant risk' of groundwater pollution (system T1A5C10, 28.4%). Most of the single pit latrines are found to be emptied within 1-2 years. Based on the household survey, variable F3 for system T1A5C10 was set to 78%.
- ✓ 7.7% of septic tanks are connected to soak pits (system T1A2C5). They are well-constructed as per the field visit observation. The risk of groundwater contamination was deemed low, therefore that option was selected in the SFD Matrix.
- ✓ Around 55% of HHs have emptied their septic tank with a soak pit with a desludging frequency of 2-5 years. Based on the household survey, variable F3 for system T1A2C5 is set to 55%.
- ✓ There are 51,9% of septic tanks connected to the open drain, water bodies, open ground and to 'don't know where' which are emptied within 2-5 years. Based on the household survey, variable F3 for systems T1A2C6, T1A2C7, T1A2C8 and T1A2C9 are set to 53%.
- ✓ Wastewater in T1A1C6 and supernatant in T1A2C6 are directly discharged into the river or the environment untreated. Therefore, variables W4c, W5c, S4e and S5e were set to 0%.
- ✓ Since there are no wastewater or faecal sludge treatment facilities in the town and all the collected FS is disposed of untreated into the environment, variables F4 and F5 for all systems are considered to be 0%.

6 List of Sources

Reports, literature and website

- Bangladesh Bureau of Statistics (BBS), 2011.
- Population and Housing Census, 2011.
- Baseline Survey of the project “Feasibility for Implementing of Solid Waste and Faecal Sludge Management System in 53 District Level Municipalities and 8 Municipalities”, Department of Public Health Engineering (DPHE), Dhaka, Bangladesh (December 2020).
- Report on ‘Hydrogeological Screening, Slug Test and Geophysical Logging on Observation Well Units’ under *Bangladesh Rural Water Supply and Sanitation Project (BRWSSP)*, Arsenic Management Division, Department of Public Health Engineering (DPHE) (March 2017)
- The revised ‘National Strategy for Water Supply and Sanitation, 2021’
- ‘At a Glance: Habiganj Municipality’, by Municipality office.
- <https://www.gps-latitude-longitude.com/gps-coordinateshttp://bmd.gov.bd/p/Rainfall-Situation-202>

Key Informant Interviews (KIIs) (September 2020 to December 2020)

- KII with Mayor, Habiganj Municipality.
- KII with Conservancy Inspector, Habiganj Municipality.
- KII with Sanitary inspector, Habiganj Municipality.
- KII with Engineer, Habiganj Municipality.
- Facilitators: Md. Mynul Islam Hemel, Field Coordinator, Tillers.



Figure 8: KIIs with different stakeholders in Habiganj. (Source: *Feasibility study 2020-21/DPHE*).

Focus Group Discussions (FGDs) (September 2020 to December 2021)

- FSM Sweepers and Service Providers.
- First Stage Solid Waste Collector.
- Slum Dwellers.



Figure 9: Focus Group Discussions in Habiganj. (Source: *Feasibility study 2020-21/DPHE*).

Additional information

- This report was compiled as part of the Baseline Survey of the project, ***“Feasibility for Implementing of Solid Waste and Faecal Sludge Management System in 53 District Level Municipalities and 8 Municipalities”***, (December 2020).
- The project was implemented under the supervision of the Department of Public Health Engineering (DPHE). In-depth information and data were collected for the towns which included project documents, master plans and baseline reports from the Municipality and national levels, statistical data like population and household income expenditure, GIS data and other geospatial data and satellite images, and open street maps (OSM). The Field Survey of the project was conducted from 01 January 2020 to 24 March 2020 and from 04 July 2020 to 30 November 2020. The field survey includes household surveys, key informant interviews, focus group discussions, and physical feature surveys. A central server has been established to monitor FSM and SWM databases under the project. The results of the study are shared with the municipal authority and are considered as a basis for preparing investment projects by the government and development partners, and sustainable plans for operating and maintaining the systems by the municipal authorities.
- We would like to thank Mr. Md. Mizanur Rahman, Mayor, Habiganj Municipality, Mr. Modhusudon Das, Executive Engineer, Habiganj Municipality, Mr. Md. Fayez Ahmed, Secretary, Habiganj Municipality for providing all the required primary and secondary data and cooperating for Key Informant Interviews (KIIs) & Focused Group Discussions (FGDs). This report would not have been possible to produce without the constant support of Mr. Md. Mizanur Rahman, Mayor, Habiganj Municipality, who helped in conducting sample surveys and FGDs in the field.
- We also acknowledge the support of the Centre for Science and Environment, India for the promotion of SFD in Bangladesh.

Habiganj Municipality, Bangladesh, 2024

Produced by:

Dr. Abdullah Al-Muyeed, Chief Operating
Officer, CWIS-FSM Support Cell

Shishir Kumar Biswas, Project Director,
Feasibility for Implementing of Solid Waste
and Faecal Sludge Management System in
53 District Level Municipalities and 8 City
Corporations, Department of Public Health
Engineering (DPHE)

Md. Tawhidur Rahaman, Technical Expert,
CWIS-FSM Support Cell

Department of Public Health Engineering
(DPHE), Bangladesh

© Copyright

All SFD Promotion Initiative materials are freely
available following the open-source concept for
capacity development and non-profit use, so long
as proper acknowledgement of the source is
made when used. Users should always give
credit in citations to the original author, source
and copyright holder.

This SFD lite report is available from:

www.sfd.susana.org

SFD Promotion Initiative

sustainable
sanitation
alliance

giz Deutsche Gesellschaft
für Internationale
Zusammenarbeit (GIZ) GmbH

On behalf of

 Federal Ministry
for Economic Cooperation
and Development


UNIVERSITY OF LEEDS

 **WORLD BANK GROUP**
Water

 **GWSP**
GLOBAL WATER
SECURITY & SANITATION
PARTNERSHIP

 **WEDC**  Loughborough
University

 **CSE**

 **eawag**
aquatic research

 **BILL & MELINDA
GATES FOUNDATION**