



*Karnataka Urban Water  
Supply & Drainage Board*



# Detailed Project Report


on

Comprehensive Underground Sewerage Scheme


for

# Mysore City





- **Extent of project area : 152.31 sqkm**
- **Population (2001): 773889**
- **Undulated Terrain between +710 - +790m MSL**
- **No. of wards :65 (MCC)**
- **Total length of streets: 2300 km**



- Trunks : 53.36 km
- Laterals: 1560 km
- Area connected with system: 70%
- Treatment plants:3 nos.

1 STP A&D : 60 MLD

2 STP B : 67.65 MLD

3 STP C : 30 MLD

**Total treatment capacity : 157.65 MLD**  
(Facultative Aerated Lagoons)

## Issues and Problems

- The proposed project is a Comprehensive and to be integrated with existing system
- The proposed system is not only for Municipal Corporation Limits it also to be taken care of Urban Sprawl / MUDA Area ;
- Identification of Missing links in the system under each drainage district.
- Rehabilitation, Strengthening and Improvement of existing sewerage system .
- Rehabilitation of existing sewage treatment plant for safe disposal., and possible options for Decentralizing the STPs as per site conditions.
- Development of techniques in operation and maintenance of sewerage system.

- Possible options for Recycle and Re-use of treated effluent and cost recovery.
- Preparation of detailed estimations and abstract for the proposals.
- Preparation of Detailed Project Report ( DPR ) and assisting the KUWS&D Board in preparing the bid documents .
- Providing 100 % connection and coverage system.



***Disturbed MH at Bamboo bazar***



***SWD with sewage flow at RMC Market***



*Sewer line bypassed with a pipe laid to connect to the drain at Pathaleeswara nagar*



*Damaged Manhole to let sewage into SWD at Kumbarkoppal*



*Sewage water flowing out from  
Manhole in Mysore University area*



*Last MH of the locality after which  
sewage  
let into SWD at Bannimantap Ph2*





***Damaged Sewer at Paduvarahalli***



***Damaged manhole letting sewage into  
SWD at Hebbal II- Stage 1***

## ▪ Identifications and findings

### ➤ District A & D (Rayankere STP catchment)

-In Paduvarahalli the branches connecting to the main line in Valmiki Road are all damaged and become defunct and they are let out in the nearby SWD running in the open land.

-In Jayalakshmipuram II stage the branch line is not connecting to the main sewer line because of the difference in the levels and it is disposed directly into the open land nearby.

-In BEML layout at one point i.e., at 9th block 9th cross the branch is not connected to any main and it just left in the open ground.

➤ District B (Vidyaranyapuram STP catchment)

-The sewer line passing through the Lingayath Smashan (Burial Ground) in Vidyaranyapuram leading to the main sewer towards STP 'B' is damaged and to be replaced.

-The sewage from Itekeguda, Manasarovar area passing through Doddu Kere Maidan is entering into a big storm water drain and it is not connected to any sewer main. The manholes in the Doddu Kere Maidan are completely damaged and overflowing.

-Ghousianagar – Insufficient capacity sewer network. Also the sewer network is not connected to main sewer instead let into SWD network.

➤ District C (Kesere STP catchment)

-The sewer passing through the RMC market in Bamboo Bazaar is completely damaged causing the market into hazardous place and the sewage enters into SWD as the existing following sewer line is defunct.

Areas located near Muslim burial ground in C V Road are not linked to the main sewer as the main sewer alignment is in burial ground is defunct as such the sewage is entering into the SWD

# Need for the Project

Identification & Providing of sewers in Missing links and Uncovered area in the system under each drainage district ..

Extension and improvement of Sewerage net work system in Newly developed and uncovered areas

Missing links in sewer net work system to be connected to the Proposed sewer main so that the sewage flows can be conveyed to the nearby STP.

Sewage in some part of the areas in each drainage district being discharged into the Storm water drain / open nallas. Transfer of storm water drain connections to the proposed Sewer mains/ branch mains & finally into the STP.

Modification of STPs & Construction of new STP's

Rehabilitation, Strengthening and Improvement of existing sewerage system .

Providing 100% coverage and connection with sewerage system to the residence of Mysore Project areas.

# Population growth Pattern

<b>Year</b>	<b>Population</b>	<b>Decadal Increase</b>	<b>Percentage increase between consecutive decades</b>
1911	71000		
		13000	18.31%
1921	84000		
		23000	27.38%
1931	107000		
		43000	40.19%
1941	150000		
		94000	62.67%
1951	244000		
		10000	4.10%
1961	254000		
		101685	40.03%
1971	355685		
		120761	33.95%
1981	476446		
		129343	27.15%
1991	605789		
		168100	27.75%
2001	773889		

## Population projections with various analytical methods

Projection method	2011	2013	2028	2043	
Arithmetic mean method	9 20 550	9 47 212	11 47 177	13 47 142	
Geometric mean method	9 20 550	9 68 166	14 13 241	20 62 922	
Incremental Increase method	9 20 550	9 48 562	11 72 982	14 22 702	
Yearly variation method	9 20 550	9 74 985	13 83 248	17 91 510	
Semilog (Analytical) method	9 20 550	10 02 833	14 33 435	20 50 560	

It is observed that the projections through **Geometric Mean method** tally with the city development Trend observed in the above table.

# Population Projections

## Sewerage District wise population projections

Zone	Area (Sq km)	2011		2013		2028		2043	
		density per Sqkm	population	density per Sqkm	projected population	density per Sqkm	projected population	density per Sqkm	projected population
Distict A	16.22	7145	115887	7529	122113	15363	249187	19504	316348
Distict B	32.83	7534	247339	7939	260626	13674	448923	16884	554302
Distict C	22.34	12303	274847	12965	289648	14406	321831	20167	450530
Distict D	31.63	4797	151734	5054	159849	6665	210810	12819	405466
Distict E	13.52	3080	41645	3246	43883	4730	63948	7643	103332
Distict F	4.99	3822	19073	4028	20098	5012	25008	10570	52746
Distict G	11.24	2847	32003	3000	33723	4372	49142	9349	105087
Other	19.53	1947	38022	2051	40060	2286	44651	3850	75189
<b>Total city</b>	<b>152.31</b>	<b>6044</b>	<b>920550</b>	<b>6369</b>	<b>970000</b>	<b>9280</b>	<b>1413500</b>	<b>13545</b>	<b>2063000</b>



	<u>year</u>	<u>projected population</u>	<u>sewage generated</u>
Base year	- 2013	9 70 000	120.35 MLD
Intermediate year	- 2028	14 13 500	177.16 MLD
Ultimate year	- 2043	20 63 000	257.26 MLD


## Issues addressed

- Proposed project is a Comprehensive and to be integrated with existing system
- Identification of Missing links in the system under each drainage district.
- Rehabilitation, Strengthening and Improvement of existing sewerage system .
- Rehabilitation of existing sewage treatment plant for safe disposal and possible options for Decentralizing the STPs as per site conditions.

contd..

## Issues addressed

- Development of techniques in operation and maintenance of sewerage system.
- Providing 100 % connection and coverage system.
- Rejuvenation of city lakes by coverage of upstream areas with UGD.
- 2 nos.of existing pumping stations have been omitted which are found not necessary as per new alignment.



 Existing STPs to be refurbished

 New STPs – Capacity 33MLD

## Proposed network

Sewerage District	Trunks	Laterals
District A	18.79	38.54
District B	23.94	102.29
District C	29.30	91.49
District D	27.23	94.54
District E	11.43	63.13
District G	18.95	59.88
<b>Total lengths</b>	<b>143.80 km</b>	<b>449.87 km</b>

Total length of Missing links : 57 km

Total length of rehabilitation : 36 km

## STPs - refurbishing

at Rayanekere for District A&D	60 MLD
at Vidyaranyapuram for District B	68 MLD
at Kesare for District C	30 MLD

Refurbishing of STPs includes replacement of Mechanical screens, introduction of mechanical degritters with raking classifiers, optimization of aerators, raising and lining of bunds, chlorination, introduction of SCADA for flow measurements, online sampling and laboratory facility etc.

**STPs - new**

at Kesare for District C 15 MLD

near Infosys for District G 8 MLD

in Bannuru Road for District E 10 MLD

Technology proposed for treatment is **Sequential Batch Reactor (SBR)** which is proven to be cost effective with better effluent characteristics.

## **House service connections**

**Making new house service connections  
and remaking damaged HSCs  
during execution**

**-59367 Nos.**



- Design period : Ultimate 30 years & Prospective 15 years
- Per capita Water Supply : 135 LPCD
- Per Capita Sewage : 80% of (135LPCD+10% from Ground water source & 5% infiltration)
- Peak Factor : Varies from 2.0 to 2.25 & 3.0.
- Minimum Velocity : 0.6 m/s
- Maximum Velocity : 2.5 m/s
- d/D Ratio : 0.8
- Pipe Material : Upto 200mm dia – SWG  
for 250 & 300 mm dia – RCC NP2  
above 350 mm – RCC NP3 S/S with SRC
- Hydraulic formula : Mannings
- Min. depth of manhole : 1.0m.
- Manholes : conventional / partially pre-fabricated,

## before UGDS:

- Raw sewage being used for Irrigation leads to health hazards,
- Effect on Ground water quality.
- Odour & Mosquito nuisance
- Public resentment

## after UGDS:

- Improvement of Health and productivity .
- Eco friendly atmosphere
- Increase in income due to increased irrigation / paragrass cultivation
- Income from recycled and reuse of treated effluent for industries.
- sludge utilization as manure for horticulture purpose
- MCC / MUDA benefits by charging cess on treated water released for irrigation.

year	Monthly service charges			New connection charges			Annual Total Revenue (Rs in lakhs)
	No. of connections	Annual weighted avg tariff	Annual Revenue (Rs in lakhs)	No. of connections	Tariff rate	Annual Revenue (Rs in lakhs)	
2011-12	142000	200	284.00	21930	2000	438.60	722.60
2012-13	146790	200	293.58	26720	2000	534.40	827.98
2013-14	151580	200	303.16	26720	2000	534.40	837.56
2014-15	156370	200	312.74	4790	2000	95.80	408.54
2015-16	161160	200	322.32	4790	2000	95.80	418.12
2016-17	165950	260	431.47	4790	2600	124.54	556.01
2017-18	170740	260	443.92	4790	2600	124.54	568.46
2018-19	175530	260	456.38	4790	2600	124.54	580.92
2019-20	180320	260	468.83	4790	2600	124.54	593.37
2020-21	185110	260	481.29	4790	2600	124.54	605.83
2021-22	189900	338	641.86	4790	3380	161.90	803.76
2022-23	194690	338	658.05	4790	3380	161.90	819.95
2023-24	199480	338	674.24	4790	3380	161.90	836.14
2024-25	204270	338	690.43	4790	3380	161.90	852.33
2025-26	209060	338	706.62	4790	3380	161.90	868.52
							<b>10300.11</b>

# MYSORE UGDS –

# O&M Expenditure Projections

year	O&M of STPs				pumping cost			Esatblishment for net work O&M @Rs 15000 per 1000 population	Total O&M costs (Rs in lakhs)
	FAL process STPs		SBR Process STPs		sewage pumped MLD	1000 KWh	amount (@Rs 5per KWh )		
	sewage (MLD)	Annual O&M costs per MLD	sewage treated (MLD)	Annual O&M costs (Rs in lakhs)					
2011-12	105.0	229.95	21.00	103.48	79.52	2628	131.40	152.52	<b>617.35</b>
2012-13	108.5	237.62	21.79	107.37	82.64	2732	143.42	165.92	<b>654.33</b>
2013-14	112.0	245.28	22.58	111.26	85.76	2836	156.32	180.29	<b>693.15</b>
2014-15	115.5	252.95	23.37	115.16	88.88	2940	170.15	195.67	<b>733.92</b>
2015-16	119.0	260.61	24.16	119.05	92.00	3043	184.97	212.14	<b>776.76</b>
2016-17	122.5	268.28	24.95	122.94	95.12	3147	200.84	229.77	<b>821.83</b>
2017-18	126.0	275.94	25.74	126.83	98.24	3251	217.84	248.63	<b>869.25</b>
2018-19	129.5	283.61	26.53	130.73	101.36	3355	236.04	268.80	<b>919.18</b>
2019-20	133.0	291.27	27.32	134.62	104.48	3459	255.52	290.37	<b>971.78</b>
2020-21	136.5	298.94	28.11	138.51	107.60	3563	276.35	313.43	<b>1027.22</b>
2021-22	140.0	306.60	28.90	142.40	110.72	3667	298.63	338.06	<b>1085.69</b>
2022-23	143.5	314.27	29.69	146.30	113.84	3770	322.44	364.37	<b>1147.38</b>
2023-24	147.0	321.93	30.48	150.19	116.96	3874	347.89	392.47	<b>1212.48</b>
2024-25	150.5	329.60	31.27	154.08	120.08	3978	375.07	422.47	<b>1281.22</b>
2025-26	154.0	337.26	32.06	157.98	123.20	4082	404.10	454.49	<b>1353.83</b>
									<b>14165.37</b>

S.No.	Description of work	Length (km)/ capacity(mld)/ no.	Amount (in lakhs)
1	Conducting Of Detailed Field Survey For Ugd System Of Existing Network & Missing Links, Along With Preparation Of Designs For Laterals / Trunks / Outfallsewer /Stp's Etc & Drawings Based On Captured Data.	1.00	143.46
2	Cost of trunk sewers of various diameter, including construction of manholes, in all the Districts of Mysore City Corporation		
	District A	18.79	1381.00
	District B	23.94	1337.70
	District C	29.30	1631.50
	District D	32.42	2333.00
	District E	11.43	879.50
	District G	18.95	998.00
	catchment 4	8.97	909.80
3	Cost of Laterals in various Districts of different diameters including construction of manholes of various depths in all the Districts of Mysore City Corporation		
	District A	38.54	897.60
	District B	102.29	2377.00
	District C	91.49	2154.90
	District D	94.54	2182.00
	District E	63.13	1467.90
	District G	59.88	1415.90
4	Construction of new STPs and Refurbishment of existing STPs including all pumps, mechanical & electrical equipments		
	District A&D Refurbishing of existing FAL process STP	60	785.00
	District B Refurbishing of existing FAL process STP to SBR technology	67.65	2430.00
	District C Refurbishing of existing FAL process STP	30	455.00
	District C new SBR process STP	15	1450.00
	District E new ASP process STP	10	675.00
	District G new SBR process STP	8	965.00

5	Providing pumping installations including rising mains, pumpsets, pump houses etc		
	District B	1	172.20
	District C	2	126.68
	District D	4	327.64
6	Providing new House service connections after developing sewer net work including restoration damaged HSCs including missing HSC's during project period @ Rs 2710 per HSC	59367	1608.85
7	Estimate For The Work Of Additional Outfall Sewer Lines At Various Places	8	1339.40
8	Providing sewer lines with trenchless technology / pipe jacking system where open excavation is not possible and at deep cuts/ railway crossings/ important road intersections	920	1380.00
9	Provision towards Public toilets		30.00
10	Provision for Sewer cleaning equipment		300.00
		Sub-Total	32154.02
11	Provisions for tender premium @ 6 % per annum for 2 years		3858.48
12	ETP @ 12 %		3858.48
13	Contingencies @ 3 %		964.62
14	Miscellaneous & rounding off including deposits to various departments etc.,		14.40
		Grand Total	40850.00
		Say Rs	408.50 Crores

**Total Project Cost : Rs. 408.50 Crores**

**Project Implementation Period : 2.5 years (30 months)**

**Funding pattern & Cash flow :**

Rs. In Crores

Contribution by	Sharing %	2013 - 2014 1 <sup>st</sup> year	2014 - 2015 2 <sup>nd</sup> year	2015 - 2016 3 <sup>rd</sup> year
Govt. of India (MOUD) (JnNURM)	80%	130.72	130.72	65.36
Govt. of Karnataka	10%	16.34	16.34	8.17
Mysore City Corporation	10%	16.34	16.34	8.17
<b>Total</b>		<b>163.40</b>	<b>163.40</b>	<b>81.70</b>

## **Advantages of the proposed Scheme**

The proposed sewerage scheme consisting of under ground sewage collection mains and decentralized and individual STPs is having the following apparent advantages:

- Since the entire project area has been divided into 7 zones, the scheme can be implemented piecemeal in accordance with the available budgets. Functionality of one zone does not affect any other zone.
- The alignment of trunk sewers along the storm water drains with provision of pathways/ inspection paths will ease out the maintenance problems so far sewerage sector faced. Since the trunk sewers run at the lowest levels of the localities there would be no sewage flows in storm water drains.



- The design of trunks and laterals make use of the available ground gradients in a big way and is most economical.
- Provision is made in the design to take care to integrate the entire net work into one comprehensive scheme.
- The scheme does not envisage disposal of the treated effluent on the downstream side, thereby eliminating interference with the downstream designs and O/M procedures.
- It is proposed to utilize the treated effluent for recreational purposes and for maintenance of green belts in the municipal area
- The provision of advanced technology treatment plants, will minimize the cost of pumping and supports the natural gradient of the terrain.

Thank you